

Gildemeister
**CTX 410 V4 -
VDI 30**



High-tech from heimatec - heimatec - Tools and systems for productive turning and milling

heimatec belongs to the international technology and quality leaders for precision tools and specializes in the development and production of high-precision static and live tools for all CNC lathes, CNC turn-/mill machines and CNC machining centers.

The range of products* spans from static BMT and VDI tool holders, live tools up to highly complex customer-specific individual solutions. heimatec, headquartered in Renchen, has a own subsidiary in Asia and India and numerous representatives as well as trading partners all over the world.

*OUR PRODCUTS

Static tool holders

Live tool units

Precision tools

Tools for turning and machining centres

Tools for swiss type lathes

Tool changing and uick-change systems

Tool systems for gear production

Digital tool management

This catalogue, including all its parts, is protected by copyright. Any use outside the restricted limitations of the Copyright Act without the consent of heimatec is inadmissible and liable to prosecution. This applies in particular to duplication, translation, microfilming and storage and processing in electronic systems.

heimatec GmbH reserves the right to make technical changes at any time without giving prior notice. This applies in particular to adjustments at any time to meet new or changed international standards, or in case of further developments of our products or manufacturing processes.

The current version of our General Terms and Conditions can be found on our website.

Part-#	Name	
8 010 25 090	Axial drilling and milling head ER 25	
	Weight [kg]:	1.580
	Tool drive:	DIN 5480
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	ER 25
	Gear ratio [i]:	1:1
	Torque max [Nm]:	25
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	EXT
	Please note:	round housing ø 68
8 010 25 091	Axial drilling and milling head ER 25 IC	
	Weight [kg]:	1.830
	Tool drive:	DIN 5480
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	ER 25
	Gear ratio [i]:	1:1
	Torque max [Nm]:	25
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	IC/Ext
	Pressure max [bar]:	25
	Please note:	round housing ø 68
8 010 25 118	Axial drilling and milling head ER 25 AX UT	
	Weight [kg]:	1.780
	Tool drive:	DIN 5480
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	ER 25 A - u-tec
	Gear ratio [i]:	1:1
	Torque max [Nm]:	25
	Rotation max [1/min]:	12000
	Rotating direction:	same
	Coolant:	EXT
	Please note:	stronger bearing
8 010 25 119	Axial drilling and milling head ER 25 AX UT IC	
	Weight [kg]:	1.780
	Tool drive:	DIN 5480
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	ER 25 A - u-tec
	Gear ratio [i]:	1:1
	Torque max [Nm]:	25
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	IC/Ext
	Pressure max [bar]:	25
	Please note:	round housing ø 68

Part-#	Name	
8 010 25 154	Axial drilling and milling head ER 25 AX UT	
	Weight [kg]:	1.830
	Tool drive:	DIN 5480
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	ER 25 A - u-tec
	Gear ratio [i]:	1:1
	Torque max [Nm]:	25
	Rotation max [1/min]:	12000
	Rotating direction:	same
	Coolant:	EXT
8 013 22 000	Axial drilling and milling head Weldon 6	
	Version:	left
	Tool drive:	DIN 5480
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	Weldon (DIN 1835 b) 6
	Gear ratio [i]:	1:2
	Torque max [Nm]:	8
	Rotation max [1/min]:	8000
	Rotating direction:	same
	Coolant:	EXT
8 013 24 014	Axial drilling and milling head Weldon 10	
	Version:	left
	Tool drive:	DIN 5480
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	Weldon (DIN 1835 b) 10
	Gear ratio [i]:	1:2
	Torque max [Nm]:	8
	Rotation max [1/min]:	8000
	Rotating direction:	same
	Coolant:	EXT
8 013 25 007	Axial drilling and milling head Weldon 16	
	Weight [kg]:	4.320
	Version:	left
	Tool drive:	DIN 5480
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	Weldon (DIN 1835 b) 16
	Gear ratio [i]:	1:2
	Torque max [Nm]:	8
	Rotation max [1/min]:	8000
	Rotating direction:	same
	Coolant:	EXT
	Please note:	stronger bearing
8 014 25 002	Axial milling head universal arbor 22	
	Tool drive:	DIN 5480
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	Universal arbor 22
	Gear ratio [i]:	2:1
	Torque max [Nm]:	40


Part-#	Name	
	Rotation max [1/min]:	3000
	Rotating direction:	same
	Coolant:	EXT
	Please note:	stronger bearing
8 018 24 002	Axial drilling and milling head ER 16 AX	
	Weight [kg]:	2.800
	Notation:	Y-axes adjustable ± 21 mm
	Tool drive:	DIN 5480
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	ER 16 A
	Gear ratio [i]:	1:1
	Torque max [Nm]:	16
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	EXT
8 019 25 008	Axial milling head universal arbor 1"	
	Weight [kg]:	5.300
	Notation:	offset
	Version:	left
	Tool drive:	DIN 5480
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	Universal arbor 1" (25,4mm)
	Gear ratio [i]:	2:1
	Torque max [Nm]:	40
	Rotation max [1/min]:	4000
	Rotating direction:	opposite
	Coolant:	EXT
	Please note:	stronger bearing
	Offset [mm]:	34,5
8 019 25 021	Axial drilling and milling head ER 25	
	Weight [kg]:	4.320
	Notation:	offset
	Version:	left
	Tool drive:	DIN 5480
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	ER 25
	Gear ratio [i]:	1:2
	Torque max [Nm]:	12
	Rotation max [1/min]:	12000
	Rotating direction:	opposite
	Coolant:	EXT
	Please note:	stronger bearing
	Offset [mm]:	34,5
8 019 25 025	Axial milling head universal arbor 22	
	Notation:	offset
	Version:	left
	Tool drive:	DIN 5480
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	Universal arbor 22
	Gear ratio [i]:	2:1

Part-#	Name
	Torque max [Nm]: 40 Rotation max [1/min]: 4000 Rotating direction: opposite Coolant: EXT Please note: stronger bearing Offset [mm]: 34,5
8 019 25 027	Axial drilling and milling head ER 25 IC
	Weight [kg]: 4.360 Notation: offset Version: left Tool drive: DIN 5480 Shank size [mm]: 30.00 Shank type: VDI Tool adaption: ER 25 Gear ratio [i]: 1:3 Torque max [Nm]: 6 Rotation max [1/min]: 15000 Rotating direction: opposite Coolant: IC/Ext Pressure max [bar]: 25 Please note: stronger bearing Offset [mm]: 34,5
8 019 26 002	Axial drilling and milling head HT 4 IC
	Weight [kg]: 4.300 Notation: offset Version: right Tool drive: DIN 5480 Shank size [mm]: 30.00 Shank type: VDI Tool adaption: HT 4 Gear ratio [i]: 1:2 Torque max [Nm]: 12 Rotation max [1/min]: 12000 Rotating direction: opposite Coolant: IC/Ext Pressure max [bar]: 25 Offset [mm]: 34,5
8 030 24 040	Radial drilling and milling head ER 20 AX
	Weight [kg]: 4.760 Version: left Tool drive: DIN 5480 Shank size [mm]: 30.00 Shank type: VDI Tool adaption: ER 20 A Gear ratio [i]: 1:2 Torque max [Nm]: 8 Rotation max [1/min]: 8000 Rotating direction: opposite Coolant: EXT Center distance [mm]: 100

Part-#	Name
8 030 25 055	Radial drilling and milling head ER 25
	Weight [kg]: 4.020
	Version: left
	Tool drive: DIN 5480
	Shank size [mm]: 30.00
	Shank type: VDI
	Tool adaption: ER 25
	Gear ratio [i]: 1:1
	Torque max [Nm]: 25
	Rotation max [1/min]: 6000
	Rotating direction: opposite
	Coolant: EXT
	Center distance [mm]: 100
8 030 25 058	Radial drilling and milling head Weldon 16 IC
	Version: left
	Tool drive: DIN 5480
	Shank size [mm]: 30.00
	Shank type: VDI
	Tool adaption: Weldon (DIN 1835 b) 16
	Gear ratio [i]: 1:1
	Torque max [Nm]: 25
	Rotation max [1/min]: 6000
	Rotating direction: opposite
	Coolant: IC/Ext
	Center distance [mm]: 100
8 030 25 087	Radial drilling and milling head ER 25
	Weight [kg]: 3.580
	Version: left
	Tool drive: DIN 5480
	Shank size [mm]: 30.00
	Shank type: VDI
	Tool adaption: ER 25
	Gear ratio [i]: 1:1
	Torque max [Nm]: 25
	Rotation max [1/min]: 6000
	Rotating direction: opposite
	Coolant: EXT
	Center distance [mm]: 85
8 030 25 118	Radial drilling and milling head ER 25 AS IC
	Version: left
	Tool drive: DIN 5480
	Shank size [mm]: 30.00
	Shank type: VDI
	Tool adaption: ER 25 A
	Gear ratio [i]: 1:1
	Torque max [Nm]: 32
	Rotation max [1/min]: 6000
	Rotating direction: opposite
	Coolant: IC/Ext
	Center distance [mm]: 85

Part-#	Name
8 030 25 136	Radial drilling and milling head ER 25 IC
	Version: left
	Tool drive: DIN 5480
	Shank size [mm]: 30.00
	Shank type: VDI
	Tool adaption: ER 25
	Gear ratio [i]: 1:1
	Torque max [Nm]: 25
	Rotation max [1/min]: 6000
	Rotating direction: opposite
	Coolant: IC/Ext
	Pressure max [bar]: 140
	Center distance [mm]: 85
8 030 26 013	Radial drilling and milling head Weldon 20 IC
	Weight [kg]: 4.620
	Version: left
	Tool drive: DIN 5480
	Shank size [mm]: 30.00
	Shank type: VDI
	Tool adaption: Weldon (DIN 1835 b) 20
	Gear ratio [i]: 1:1
	Torque max [Nm]: 25
	Rotation max [1/min]: 6000
	Rotating direction: opposite
	Coolant: IC/Ext
	Please note: stronger bearing
	Center distance [mm]: 100
8 030 26 055	Radial drilling and milling head HT 4
	Weight [kg]: 4.820
	Version: left
	Tool drive: DIN 5480
	Shank size [mm]: 30.00
	Shank type: VDI
	Tool adaption: HT 4
	Gear ratio [i]: 1:3
	Torque max [Nm]: 8
	Rotation max [1/min]: 15000
	Rotating direction: opposite
	Coolant: EXT
	Center distance [mm]: 100
8 030 26 140	Radial drilling and milling head HT 4 IC air
	Weight [kg]: 4.680
	Version: left
	Tool drive: DIN 5480
	Shank size [mm]: 30.00
	Shank type: VDI
	Tool adaption: HT 4
	Gear ratio [i]: 1:3
	Torque max [Nm]: 8
	Rotation max [1/min]: 15000
	Rotating direction: opposite
	Coolant: IC air
	Pressure max [bar]: 10
	Center distance [mm]: 85

Part-#	Name	
8 031 24 029	Radial milling head universal arbor 16	
	Version:	left
	Tool drive:	DIN 5480
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	Universal arbor 16
	Gear ratio [i]:	1:1
	Torque max [Nm]:	25
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	EXT
	Center distance [mm]:	85
8 031 26 016	Radial milling head universal arbor 27	
	Weight [kg]:	3.430
	Version:	left
	Tool drive:	DIN 5480
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	Universal arbor 27
	Gear ratio [i]:	1:1
	Torque max [Nm]:	25
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	EXT
	Please note:	stronger bearing
	Center distance [mm]:	64
8 033 25 106	Radial drilling and milling head ER 25 IC	
	Notation:	offset
	Version:	left
	Tool drive:	DIN 5480
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	ER 25
	Gear ratio [i]:	1:1
	Torque max [Nm]:	25
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	IC/Ext
	Pressure max [bar]:	140
	Center distance [mm]:	100
8 033 26 008	Radial drilling and milling head HT 4	
	Weight [kg]:	4.020
	Notation:	offset
	Version:	left
	Tool drive:	DIN 5480
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	HT 4
	Gear ratio [i]:	1:1
	Torque max [Nm]:	25
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	EXT
	Center distance [mm]:	85



Part-#	Name	
8 033 26 015	Radial drilling and milling head HT 4 IC air	
	Weight [kg]:	4.280
	Notation:	offset
	Version:	left
	Tool drive:	DIN 5480
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	HT 4
	Gear ratio [i]:	1:2
	Torque max [Nm]:	8
	Rotation max [1/min]:	10000
	Rotating direction:	same
	Coolant:	IC air
	Pressure max [bar]:	10
	Center distance [mm]:	85
8 033 26 017	Radial drilling and milling head HT 4 IC	
	Weight [kg]:	5.860
	Notation:	offset
	Version:	left
	Tool drive:	DIN 5480
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	HT 4
	Gear ratio [i]:	1:3
	Torque max [Nm]:	8
	Rotation max [1/min]:	12000
	Rotating direction:	same
	Coolant:	IC/Ext
	Pressure max [bar]:	25
	Center distance [mm]:	100
8 036 25 002	Radial drilling and milling head ER 25 IC	
	Weight [kg]:	3.990
	Version:	doubletoothed
	Tool drive:	DIN 5480
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	ER 25
	Gear ratio [i]:	1:1
	Torque max [Nm]:	25
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	IC/Ext
	Pressure max [bar]:	140
	Center distance [mm]:	100
8 036 25 003	Radial drilling and milling head ER 25	
	Weight [kg]:	3.990
	Version:	doubletoothed
	Tool drive:	DIN 5480
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	ER 25
	Gear ratio [i]:	1:1
	Torque max [Nm]:	25
	Rotation max [1/min]:	6000
	Rotating direction:	opposite

Part-#	Name	
	Coolant:	EXT
	Center distance [mm]:	100
8 036 25 041	Radial drilling and milling head ER 25 AX UT	
	Weight [kg]:	4.220
	Notation:	180° reversible
	Version:	doubletoothed
	Tool drive:	DIN 5480
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	ER 25 A - u-tec
	Gear ratio [i]:	1:1
	Torque max [Nm]:	25
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	EXT
	Please note:	stronger bearing
	Center distance [mm]:	100
8 036 25 042	Radial drilling and milling head ER 25 AX UT IC	
	Weight [kg]:	4.640
	Notation:	180° reversible
	Version:	doubletoothed
	Tool drive:	DIN 5480
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	ER 25 A - u-tec
	Gear ratio [i]:	1:1
	Torque max [Nm]:	25
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	IC/Ext
	Pressure max [bar]:	140
	Please note:	stronger bearing
	Center distance [mm]:	100
8 040 24 012	Universal head ± 90° adjustable ER 20	
	Weight [kg]:	2.470
	Version:	right
	Tool drive:	DIN 5480
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	ER 20
	Gear ratio [i]:	1:1
	Torque max [Nm]:	10
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	EXT
	Please note:	Fixation 180° reversible
	Center distance [mm]:	64
8 040 24 035	Universal head ± 90° adjustable ER 16	
	Weight [kg]:	2.320
	Version:	right
	Tool drive:	DIN 5480
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	ER 16

Part-#	Name
	Gear ratio [i]: 1:1 Torque max [Nm]: 10 Rotation max [1/min]: 6000 Rotating direction: same Coolant: EXT Please note: Fixation 180° reversible Center distance [mm]: 64
8 040 24 059	Universal head ± 90° adjustable ER 16 AX UT
	Weight [kg]: 4.430 Version: left Tool drive: DIN 5480 Shank size [mm]: 30.00 Shank type: VDI Tool adaption: ER 16 A - u-tec Gear ratio [i]: 1:2 Torque max [Nm]: 12 Rotation max [1/min]: 12000 Rotating direction: opposite Coolant: EXT Center distance [mm]: 88
8 040 24 075	Universal head ± 90° adjustable ER 16 AX UT IC
	Weight [kg]: 4.450 Version: left Tool drive: DIN 5480 Shank size [mm]: 30.00 Shank type: VDI Tool adaption: ER 16 A - u-tec Gear ratio [i]: 1:1 Torque max [Nm]: 25 Rotation max [1/min]: 6000 Rotating direction: opposite Coolant: IC/Ext Pressure max [bar]: 140 Center distance [mm]: 88
8 040 24 077	Universal head ± 90° adjustable ER 16 AX UT
	Version: left Tool drive: DIN 5480 Shank size [mm]: 30.00 Shank type: VDI Tool adaption: ER 16 A - u-tec Gear ratio [i]: 1:1 Torque max [Nm]: 25 Rotation max [1/min]: 6000 Rotating direction: opposite Coolant: EXT Center distance [mm]: 88
8 040 24 078	Universal head ± 90° adjustable ER 16 AX UT IC
	Version: left Tool drive: DIN 5480 Shank size [mm]: 30.00 Shank type: VDI Tool adaption: ER 16 A - u-tec Gear ratio [i]: 1:2 Torque max [Nm]: 12

Part-#	Name
	Rotation max [1/min]: 12000 Rotating direction: opposite Coolant: IC/Ext Pressure max [bar]: 140 Center distance [mm]: 88
8 040 24 079	Universal head ± 90° adjustable ER 16 AX UT
	Version: right Tool drive: DIN 5480 Shank size [mm]: 30.00 Shank type: VDI Tool adaption: ER 16 A - u-tec Gear ratio [i]: 1:1 Torque max [Nm]: 25 Rotation max [1/min]: 6000 Rotating direction: opposite Coolant: EXT Center distance [mm]: 88
8 040 24 081	Universal head ± 90° adjustable ER 16 AX UT IC
	Weight [kg]: 4.450 Version: right Tool drive: DIN 5480 Shank size [mm]: 30.00 Shank type: VDI Tool adaption: ER 16 A - u-tec Gear ratio [i]: 1:1 Torque max [Nm]: 25 Rotation max [1/min]: 6000 Rotating direction: opposite Coolant: IC/Ext Pressure max [bar]: 140 Center distance [mm]: 88
8 040 24 084	Universal head ± 90° adjustable ER 16 AX UT
	Weight [kg]: 4.440 Version: right Tool drive: DIN 5480 Shank size [mm]: 30.00 Shank type: VDI Tool adaption: ER 16 A - u-tec Gear ratio [i]: 1:2 Torque max [Nm]: 12 Rotation max [1/min]: 12000 Rotating direction: opposite Coolant: EXT Center distance [mm]: 88
8 040 24 087	Universal head ± 90° adjustable ER 16 AX UT IC
	Version: right Tool drive: DIN 5480 Shank size [mm]: 30.00 Shank type: VDI Tool adaption: ER 16 A - u-tec Gear ratio [i]: 1:2 Torque max [Nm]: 12 Rotation max [1/min]: 12000 Rotating direction: opposite

Gildemeister

CTX 410 V4 - VDI 30

Part-#	Name
	Coolant: IC/Ext Pressure max [bar]: 140 Center distance [mm]: 88
8 040 24 108	Universal head ± 90° adjustable ER 16 AX UT
	Weight [kg]: 4.470 Version: left, at +45° position can be pinned Tool drive: DIN 5480 Shank size [mm]: 30.00 Shank type: VDI Tool adaption: ER 16 A - u-tec Gear ratio [i]: 1:2 Torque max [Nm]: 12 Rotation max [1/min]: 12000 Rotating direction: opposite Coolant: EXT Center distance [mm]: 88
8 040 25 021	Universal head ± 90° adjustable ER 25 AX UT
	Weight [kg]: 4.630 Version: left Tool drive: DIN 5480 Shank size [mm]: 30.00 Shank type: VDI Tool adaption: ER 25 A - u-tec Gear ratio [i]: 1:1 Torque max [Nm]: 25 Rotation max [1/min]: 6000 Rotating direction: opposite Coolant: EXT Please note: stronger bearing Center distance [mm]: 88
8 040 25 022	Universal head ± 90° adjustable ER 25 AX UT IC
	Weight [kg]: 4.650 Version: left Tool drive: DIN 5480 Shank size [mm]: 30.00 Shank type: VDI Tool adaption: ER 25 A - u-tec Gear ratio [i]: 1:1 Torque max [Nm]: 25 Rotation max [1/min]: 6000 Rotating direction: opposite Coolant: IC/Ext Pressure max [bar]: 140 Please note: stronger bearing Center distance [mm]: 88
8 040 25 040	Universal head ± 90° adjustable ER 25 AX UT IC
	Weight [kg]: 3.500 Version: right Tool drive: DIN 5480 Shank size [mm]: 30.00 Shank type: VDI Tool adaption: ER 25 A - u-tec Gear ratio [i]: 1:1 Torque max [Nm]: 25

Gildemeister

CTX 410 V4 - VDI 30

Part-#	Name	
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	IC/Ext
	Pressure max [bar]:	140
	Please note:	stronger bearing
	Center distance [mm]:	88
8 200 20 000	Plug Z2-30 K	
	Weight [kg]:	0.060
	Shank size [mm]:	30.00
	Shank type:	VDI
8 200 20 005	Plug Z2-30 S	
	Weight [kg]:	0.740
	Shank size [mm]:	30.00
	Shank type:	VDI
8 202 20 012	Basic holder longitudinal seat FN 12	
	Weight [kg]:	1.160
	Version:	universal
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	Interface FN 12
	Coolant:	EXT
8 209 22 006	Adapter for VDI 30	
	Weight [kg]:	4.000
	Version:	left
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	DIN 69880 - 30
	Coolant:	EXT
	Please note:	demountable in right version
	Center distance [mm]:	85
8 210 26 011	Tool holder HT 4 IC	
	Weight [kg]:	1.270
	Version:	right
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	HT 4
	Coolant:	IC/Ext
8 210 26 012	Tool holder HT 4 IC	
	Version:	left
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	HT 4
	Coolant:	IC/Ext
8 215 22 000	Tool holder C2-30x20	
	Weight [kg]:	1.980
	Employment for:	VDI 30
	Version:	left
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	Sq. 20/16

Gildemeister

CTX 410 V4 - VDI 30

Part-#	Name	
	Coolant:	EXT
8 215 22 001	Tool holder C4-30x20	
	Employment for:	VDI 30
	Version:	left
	Shank type:	VDI
	Tool adaption:	Sq. 20/16
	Coolant:	EXT
8 231 25 000	Collet chuck holder ER 25	
	Weight [kg]:	3.880
	Version:	left
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	ER 25
	Coolant:	IC/Ext
	Please note:	demountable in right version
	Center distance [mm]:	100
8 231 26 011	Tool holder HT 4	
	Version:	left
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	HT 4
	Coolant:	IC/Ext
	Please note:	demountable in right version
	Center distance [mm]:	100
8 231 26 027	Boring bar holder Ø 20	
	Version:	left
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	Ø 20
	Coolant:	IC/Ext
	Please note:	demountable in right version
	Center distance [mm]:	100
8 231 27 004	Boring bar holder Ø 25	
	Weight [kg]:	3.400
	Version:	left
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	Ø 25
	Coolant:	IC/Ext
	Please note:	demountable in right version
	Center distance [mm]:	85
8 234 24 003	Combi facing holder 30x20x 92	
	Weight [kg]:	4.750
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	Sq. 20
	Coolant:	EXT



Gildemeister

CTX 410 V4 - VDI 30

Part-#	Name	
8 235 22 000	Tool holder B2-30x20x40	
	Employment for:	VDI 30
	Version:	left
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	Sq. 20/16
	Coolant:	EXT
8 235 22 001	Tool holder B2-30x20x60	
	Employment for:	VDI 30
	Version:	left
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	Sq. 20/16
	Coolant:	EXT
8 235 22 002	Tool holder B4-30x20x40	
	Weight [kg]:	1.360
	Employment for:	VDI 30
	Version:	left
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	Sq. 20/16
	Coolant:	EXT
8 235 22 003	Tool holder B4-30x20x60	
	Employment for:	VDI 30
	Version:	left
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	Sq. 20/16
	Coolant:	EXT
8 235 22 004	Tool holder B6-30x20x40	
	Weight [kg]:	1.860
	Version:	Left
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	Sq. 20/16
	Coolant:	EXT
8 235 22 005	Tool holder B6-30x20x60	
	Weight [kg]:	2.450
	Version:	Left
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	Sq. 20/16
	Coolant:	EXT
8 235 22 006	Tool holder B8-30x20x40	
	Weight [kg]:	1.880
	Version:	Left
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	Sq. 20/16
	Coolant:	EXT

Part-#	Name	
8 235 22 007	Tool holder B8-30x20x60	
	Version:	Left
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	Sq. 20/16
	Coolant:	EXT
8 274 22 000	Tool holder D2-30x20	
	Weight [kg]:	2.220
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	Sq. 20/16
	Coolant:	EXT
8 274 22 001	Tool holder D1-30x20	
	Weight [kg]:	2.040
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	Sq. 20/16
	Coolant:	EXT
8 320 22 019	Cut-off holder, height adjustable SH 26 IC	
	Weight [kg]:	1.510
	Version:	universal
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	Clampshaft SH 26
	Coolant:	IC/Ext
	Pressure max [bar]:	70
8 320 23 013	Cut-off holder, height adjustable SH 32 IC	
	Weight [kg]:	1.720
	Version:	universal
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	Clampshaft SH 32
	Coolant:	IC/Ext
	Pressure max [bar]:	70
8 320 23 018	Cut-off holder, height adjustable SH 32 IC	
	Weight [kg]:	1.910
	Version:	universal
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	Clampshaft SH 32
	Coolant:	IC/Ext
	Pressure max [bar]:	70
	Please note:	Clampshaft internal
8 320 23 038	Cut-off holder, height adjustable SH 32 IC	
	Weight [kg]:	1.900
	Version:	universal
	Shank size [mm]:	30.00
	Shank type:	VDI
	Tool adaption:	Clampshaft SH 32
	Coolant:	IC/Ext
	Pressure max [bar]:	70

Gildemeister

CTX 410 V4 - VDI 30



Part-#	Name
--------	------

Please note:

Clampshaft internal, check applicability!

8 320 29 002 **Cut-off holder, height adjustable 845 IC**

Weight [kg]:

1.630

Version:

universal

Shank size [mm]:

30.00

Shank type:

VDI

Tool adaption:

 System 845

Coolant:

IC

Pressure max [bar]:

70



● heimatec overseas branches

○ global representations of heimatec

heimatec[®]

heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
77871 Renchen
Germany

T +49 7843 9466 0
www.heimatec.com
info@heimatec.com

Please find the contact details of our worldwide trading partners on our website:
<https://heimatec.com/business-partners>