


Axial-Bohr-und Fräskopf

Axial drilling and milling head

Tête de perçage et de fraisage axiale



Darstellung symbolisch
symbolical drawing
schéma symbolique



Optionen :
options :
options :



Dichtscheiben
sealings
joints




Spannzangen
collets
Les pinces




Wechseleinsatz u-tec
insert u-tec
insert u-tec



Bedienschlüsselsatz
set of wrench
jeu de clés



ER 25 A UT (0,5 - 16,0)



bei externer Kühlmittelzufuhr Schraube entfernen
for external coolant supply, take off screw
pour arrosage externe, enlevez la vis

» weitere Ausführungen auf Anfrage
other models on request
autres modèles sur demande

subject to technical changes

$i \neq 1$

mit innerer Kühlmittelzufuhr für Hochdruck
internal coolant supply (for high pressure)
arrosage interne (pour haute pression)

mit kombinierter Kühlmittelzufuhr
with combined coolant supply
arrosage combiné

p x n Diagramm D 00 010
p x n diagram D 00 010
p x n diagramme D 00 010

Befestigungsschrauben
fastening screws
vis de fixation

p max. [bar] = 140
i = 1:2
M₂ max. [Nm] = 40
n₂ max. [min⁻¹] = 12000

Bestell - Nr.
ref.no. / No.de cde.

8 019 65 018

nous nous réservons toutes modifications techniques