


ohne Kühlmittel
without coolant
sans arrosage

Winkelkopf

Angle head

Tête angulaire



Darstellung symbolisch
symbolical drawing
schéma symbolique

Winkelkopf 7 033 66 018
angle head 7 033 66 018
tête angulaire 7 033 66 018




360° drehbar
360° turnable
pivotable à 360°

Skalierung
graduation
graduation

Gehäusenull
gauge line of housing
cote zéro-corps de porte

Arreterring muss beim
Kunden eingestellt werden
ring has to be adjusted
by customer
la bague d'arrêt doit être
ajustée par le client


DIN 69871 - A 50




Lage der Drehmomentstütze kann zu den
Nuten der Welle eingestellt werden
Position of the location device can be
adjusted to the slots at the taper
La position du segment d'arrêt peut être
ajustée à la rainure du cône

Drehmomentstütze 7 789 99 114
location device 7 789 99 114
segment d'arrêt 7 789 99 114

Stopp-Block 7 742 99 049
stop-bloc 7 742 99 049
stop-bloc 7 742 99 049



» weitere Ausführungen auf Anfrage
other models on request
autres modèles sur demande
subject to technical changes



i = 1:1
M₂ max. [Nm] = 50
n₂ max. [min⁻¹] = 6000

Bestell - Nr.
ref.no. / No.de cde.
7 033 66 019

Optionen :
options :
options :



Spannzangen
collets
les pinces



Gewindebohrzangen
tapping collets
pinces de taraudage



Bedienschlüsselsatz
set of wrench
jeu de clés

Technische Änderung vorbehalten

nous nous réservons toutes modifications techniques