

**TOPSELLER -**  
many more available!

Live Tools


**heimatec**®

# Hyundai-WIA


## L 300 MSA/LMSA/MSD

| Part-#                                  | Tool adaption          | Rotation<br>max [1/min] | Gear ratio | Coolant | Pressure<br>max. | Center<br>distance |
|-----------------------------------------|------------------------|-------------------------|------------|---------|------------------|--------------------|
| <b>Axial drilling and milling head</b>  |                        |                         |            |         |                  |                    |
| 8 010 66 143                            | <b>ER 32 A - u-tec</b> | 12.000                  | 1:1        | IC/Ext  | 100 bar          | --                 |
| 8 010 66 145                            | <b>ER 32 A - u-tec</b> | 12.000                  | 1:1        | EXT     | 140 bar          | --                 |
| <b>Radial drilling and milling head</b> |                        |                         |            |         |                  |                    |
| 8 030 66 269                            | <b>ER 32 A - u-tec</b> | 10.000                  | 1:1        | EXT     | --               | <b>100 mm</b>      |
| 8 030 66 270                            | <b>ER 32 A - u-tec</b> | 10.000                  | 1:1        | IC/Ext  | 140 bar          | <b>100 mm</b>      |
| <b>Universal head, offset</b>           |                        |                         |            |         |                  |                    |
| 8 043 65 000                            | <b>ER 25 A - u-tec</b> | 6.000                   | 1:1        | EXT     | --               | <b>69 mm</b>       |
| 8 043 65 004                            | <b>ER 25 A - u-tec</b> | 6.000                   | 1:1        | IC/Ext  | 140 bar          | <b>69 mm</b>       |


*Illustrations similar.*




8 010 66 143




8 010 66 145



8 030 66 269



8 030 66 270



8 043 65 000

**TOPSELLER -**  
many more available!

Static Tools

**heimatec**®

# Hyundai-WIA

## L 300 MSA/LMSA/MSA

| Part-# | Tool adaption | Coolant | Pressure max. | Center distance |
|--------|---------------|---------|---------------|-----------------|
|--------|---------------|---------|---------------|-----------------|

### Universal turning holder

|              |               |        |         |    |
|--------------|---------------|--------|---------|----|
| 8 224 15 006 | <b>Sq. 25</b> | EXT    | 80 bar  | -- |
| 8 224 15 053 | <b>Sq. 25</b> | IC/Ext | 140 bar | -- |

### Boring bar holder

|              |             |        |         |               |
|--------------|-------------|--------|---------|---------------|
| 8 240 17 044 | <b>Ø 25</b> | IC/Ext | --      | <b>72 mm</b>  |
| 8 240 17 050 | <b>Ø 25</b> | IC/Ext | --      | <b>100 mm</b> |
| 8 240 18 049 | <b>Ø 32</b> | IC/Ext | 80 bar  | <b>100 mm</b> |
| 8 240 19 043 | <b>Ø 40</b> | IC/Ext | 140 bar | <b>100 mm</b> |
| 8 240 19 051 | <b>Ø 50</b> | IC/Ext | 80 bar  | <b>100 mm</b> |


### Combi facing holder

|              |               |     |        |    |
|--------------|---------------|-----|--------|----|
| 8 244 15 005 | <b>Sq. 25</b> | EXT | 80 bar | -- |
|--------------|---------------|-----|--------|----|

### Cut-off holder, height adjustable

|              |                         |        |         |    |
|--------------|-------------------------|--------|---------|----|
| 8 320 13 005 | <b>Clampshaft SH 32</b> | IC/Ext | 140 bar | -- |
|--------------|-------------------------|--------|---------|----|


*Illustrations similar.*



8 224 15 006




8 224 15 053



8 240 17 044



8 244 15 005



8 320 13 005