

TOPSELLER -
many more available!

Live Tools

heimatec®

Doosan

Lynx 2600 Y/SY - 12-fach Revolver

Part-#	Tool adaption	Rotation max [1/min]	Gear ratio	Coolant	Pressure max.	Center distance
--------	---------------	-------------------------	------------	---------	------------------	--------------------

Axial drilling and milling head

8 010 55 039	ER 25 A - u-tec	12.000	1:1	EXT	140 bar	--
8 010 55 057	ER 25 A - u-tec	12.000	1:1	IC/Ext	100 bar	--
8 010 56 039	ER 32 A - u-tec	6.000	1:1	EXT	--	--
8 010 56 089	ER 32 A - u-tec	12.000	1:1	IC/Ext	100 bar	--
8 010 56 118	heimatec Capto™ C 4	6.000	1:1	EXT	--	--
8 010 56 119	heimatec Capto™ C 4	6.000	1:1	IC/Ext	100 bar	--

Axial drilling and milling head, offset

8 019 55 054	ER 25 A - u-tec	6.000	1:1	IC/Ext	140 bar	--
--------------	------------------------	-------	-----	--------	---------	----

Radial drilling and milling head

8 030 55 255	ER 25 A - u-tec	12.000	1:1	EXT	140 bar	85 mm
8 030 56 173	ER 32 A - u-tec	6.000	2:1	EXT	--	85 mm
8 030 56 246	ER 32 A - u-tec	12.000	1:1	IC/Ext	140 bar	85 mm
8 030 56 247	ER 32 A - u-tec	12.000	1:1	EXT	--	85 mm


Radial drilling and milling head, double spindle

8 039 55 026	ER 25 A - u-tec	12.000	1:1	EXT	--	85 mm
8 039 56 029	ER 32 A - u-tec	12.000	1:1	EXT	--	85 mm


Universal head, offset

8 043 54 006	ER 16 A - u-tec	6.000	1:1	EXT	--	50 mm
8 043 55 005	ER 25 A - u-tec	6.000	1:1	EXT	--	50 mm


Illustrations similar.




8 010 55 039




8 019 55 054



8 030 55 255



8 039 55 026



8 043 54 006

TOPSELLER -
many more available!

Static Tools


heimatec®

Doosan

Lynx 2600 Y/SY - 12-fach Revolver

Part-#	Tool adaption	Coolant	Pressure max.
Cut-off holder			
8 224 03 003	Clampshaft SH 32	EXT	--
Universal turning holder			
8 224 04 062	Sq. 20	IC/Ext	100 bar
Combi facing holder			
8 244 05 003	Sq. 25	EXT	80 bar
Double turning holder			
8 251 05 001	Sq. 25	EXT	80 bar
Double boring bar holder			
8 253 07 011	Ø 25	IC/Ext	80 bar
Multiple turning holder			
8 259 04 007	Sq. 20	IC/Ext	--
Cut-off holder, height adjustable			
8 320 03 008	Clampshaft SH 32	IC/Ext	140 bar
8 320 03 025	Clampshaft SH 32	IC/Ext	70 bar


Illustrations similar.




8 224 03 003




8 224 04 062



8 244 05 003



8 251 05 001



8 253 07 011