

TOPSELLER -
many more available!

Live Tools

heimatec®

SMEC

SL 1500 M

Part-#	Tool adaption	Rotation max [1/min]	Gear ratio	Coolant	Pressure max.	Center distance
Axial drilling and milling head						
8 010 55 039	ER 25 A - u-tec	12.000	1:1	EXT	140 bar	--
8 010 55 057	ER 25 A - u-tec	12.000	1:1	IC/Ext	100 bar	--
8 010 56 039	ER 32 A - u-tec	6.000	1:1	EXT	--	--
8 010 56 089	ER 32 A - u-tec	12.000	1:1	IC/Ext	100 bar	--
8 010 56 118	heimatec Capto™ C 4	6.000	1:1	EXT	--	--
8 010 56 119	heimatec Capto™ C 4	6.000	1:1	IC/Ext	100 bar	--
Axial drilling and milling head, offset						
8 019 55 054	ER 25 A - u-tec	6.000	1:1	IC/Ext	140 bar	--
Radial drilling and milling head						
8 030 55 175	ER 25 A - u-tec	12.000	1:1	EXT	--	60 mm
8 030 55 176	ER 25 A - u-tec	12.000	1:1	IC/Ext	140 bar	60 mm
Universal head, offset						
8 043 54 006	ER 16 A - u-tec	6.000	1:1	EXT	--	50 mm
8 043 55 005	ER 25 A - u-tec	6.000	1:1	EXT	--	50 mm


Illustrations similar.



8 010 55 039




8 010 55 057



8 019 55 054



8 030 55 175



8 043 54 006

TOPSELLER -
many more available!

Static Tools


heimatec®

SMEC


SL 1500 M

Part-#	Tool adaption	Coolant	Pressure max.
Cut-off holder			
8 224 03 003	Clampshaft SH 32	EXT	--
Universal turning holder			
8 224 04 062	Sq. 20	IC/Ext	100 bar
8 224 05 029	Sq. 25	IC/Ext	140 bar
Combi facing holder			
8 244 05 003	Sq. 25	EXT	80 bar
Cut-off holder, height adjustable			
8 320 03 008	Clampshaft SH 32	IC/Ext	140 bar
8 320 03 025	Clampshaft SH 32	IC/Ext	70 bar

Illustrations similar.




8 224 03 003




8 224 04 062



8 224 05 029



8 244 05 003



8 320 03 008