


Axial-Bohr-und Fräskopf

Axial drilling and milling head

Tête de perçage et de fraisage axiale



Darstellung symbolisch
symbolical drawing
schéma symbolique

72 [2,83]
62,5 [2,46]

Optionen :
options :
options :



Dichtscheiben
sealings
joints



Spannzangen
collets
les pinces



Wechseleinsatz u-tec
insert u-tec
insert u-tec



Bedienschlüsselsatz
set of wrench
jeu de clés

ER 25 A UT (0,5 [0,020] – 16,0 [0,630])

Befestigungsschrauben
fastening screws
vis de fixation

p x n Diagramm D 00 010
p x n diagram D 00 010
p x n diagramme D 00 010

mit innerer Kühlmittelzufuhr für Hochdruck
internal coolant supply (for high pressure)
arrosage interne (pour haute pression)

mit kombinierter Kühlmittelzufuhr
with combined coolant supply
arrosage combiné

$$n_2 = -\frac{1}{j} \times n_1$$

bei externer Kühlmittelzufuhr
Schraube entfernen

for external coolant supply,
take off screw

pour arrosage externe,
enlevez la vis

$$p_{\text{max.}} [\text{bar/psi}] = 140 / (2030)$$
$$i = 1.2$$

$M_2 \text{ max. [Nm]} = 25$

$$n_2 \text{ max. } [\text{min}^{-1}] = 12000$$

Bestell - Nr.
ref.no. / No.de cde.

8 019 45 163

nous nous réservons toutes modifications techniques

Stand: 01.08.2025 / saf
DIN-A4 31.07.2025 /

02
000-049-028