

TOPSELLER -
many more available!

Live Tools

heimatec®

SMEC


SL 2000 SY - BMT 55

Part-#	Tool adaption	Rotation max [1/min]	Gear ratio	Coolant	Pressure max.	Center distance
Axial drilling and milling head						
8 010 55 039	ER 25 A - u-tec	12.000	1:1	EXT	140 bar	--
8 010 55 057	ER 25 A - u-tec	12.000	1:1	IC/Ext	100 bar	--
8 010 56 039	ER 32 A - u-tec	6.000	1:1	EXT	--	--
8 010 56 089	ER 32 A - u-tec	12.000	1:1	IC/Ext	100 bar	--
8 010 56 118	heimatec Capto™ C 4	6.000	1:1	EXT	--	--
8 010 56 119	heimatec Capto™ C 4	6.000	1:1	IC/Ext	100 bar	--
Axial drilling and milling head, offset						
8 019 55 054	ER 25 A - u-tec	6.000	1:1	IC/Ext	140 bar	--
Radial drilling and milling head						
8 030 55 175	ER 25 A - u-tec	12.000	1:1	EXT	--	60 mm
8 030 55 176	ER 25 A - u-tec	12.000	1:1	IC/Ext	140 bar	60 mm
8 030 55 102	ER 25 A - u-tec	12.000	1:1	EXT	140 bar	70 mm
8 030 55 120	ER 25 A - u-tec	12.000	1:1	IC/Ext	140 bar	70 mm
8 030 56 056	ER 32 A - u-tec	12.000	1:1	IC/Ext	140 bar	70 mm
8 030 56 274	ER 32 A - u-tec	12.000	1:1	EXT	--	70 mm
Radial drilling and milling head, double spindle						
8 039 55 051	ER 25 A - u-tec	12.000	1:1	EXT	--	60 mm
8 039 56 022	ER 32 A - u-tec	12.000	1:1	EXT	--	70 mm
Universal head, offset						
8 043 54 006	ER 16 A - u-tec	6.000	1:1	EXT	--	50 mm
8 043 55 005	ER 25 A - u-tec	6.000	1:1	EXT	--	50 mm

Illustrations similar.




8 010 55 039




8 019 55 054



8 030 55 175



8 039 55 051



8 043 54 006

TOPSELLER -
many more available!

Static Tools


heimatec®

SMEC

SL 2000 SY - BMT 55

Part-#	Tool adaption	Coolant	Pressure max.	Center distance
Cut-off holder				
8 224 03 003	Clampshaft SH 32	EXT	--	--
Universal turning holder				
8 224 04 062	Sq. 20	IC/Ext	100 bar	--
8 224 05 029	Sq. 25	IC/Ext	140 bar	--
Boring bar holder				
8 240 07 069	Ø 25	IC/Ext	--	70 mm
8 240 08 002	Ø 32	IC/Ext	140 bar	70 mm
8 240 09 009	Ø 40	IC/Ext	80 bar	70 mm
Combi facing holder				
8 244 05 003	Sq. 25	EXT	80 bar	--
Combi multiple holder				
8 251 03 012	Sq. 3/4" (19,05mm)	IC/Ext	100 bar	--
Double turning holder				
8 251 05 001	Sq. 25	EXT	80 bar	--
8 251 05 012	Sq. 25	IC/Ext	100 bar	--
Double boring bar holder				
8 253 07 011	Ø 25	IC/Ext	80 bar	--
8 253 07 047	Ø 25	IC/Ext	--	--
8 253 08 002	Ø 32	IC/Ext	--	--
Multiple turning holder				
8 259 04 007	Sq. 20	IC/Ext	--	--

Illustrations similar.




8 224 03 003




8 224 04 062



8 240 07 069



8 244 05 003



8 251 03 012

TOPSELLER -
many more available!

Static Tools

heimatec®

SMEC


SL 2000 SY - BMT 55

Part-#	Tool adaption	Coolant	Pressure max.	Center distance
--------	---------------	---------	---------------	-----------------


Cut-off holder, height adjustable

8 320 03 008	Clampshaft SH 32	IC/Ext	140 bar	--
8 320 03 025	Clampshaft SH 32	IC/Ext	70 bar	--

Illustrations similar.



8 320 03 008



8 320 03 025