



Winkelkopf

Angle head

Tête angulaire



Darstellung symbolisch
symbolical drawing
schéma symbolique




Lage der Drehmomentstütze kann zu den
Nuten der Welle eingestellt werden
Position of the location device can be
adjusted to the slots at the taper
La position du segment d'arrêt peut être
ajustée à la rainure du cône

Winkelkopf 7 033 65 003
angle head 7 033 65 003
tête angulaire 7 033 65 003

360° drehbar
360° turnable
pivotable à 360°

Skalierung
graduation
graduation



Gehäusenull
gauge line of housing
cote zéro-corps de porte



Arreterring muß beim
Kunden eingestellt werden
ring has to be adjusted
by customer
La bague d'arrêt doit être
ajustée par le client

DIN 69871 A - SK 50

Drehmomentstütze 7 744 99 115
location device 7 744 99 115
segment d'arrêt 7 744 99 115



Optionen :
options :
options :




Spannzangen
collets
les pinces



Gewindebohrzangen
tapping collets
pinces de taraudage



Wechseleinsatz u-tec
insert u-tec
insert u-tec



Bedienschlüsselsatz
set of wrench
jeu de clés

» weitere Ausführungen auf Anfrage
other models on request
autres modèles sur demande
subject to technical changes

ohne Kühlmittel
without coolant
sans arrosage

i = 1:1
M₂ max. [Nm] = 40
n₂ max. [min⁻¹] = 8000

Bestell - Nr.
ref.no. / Node cde.

7 033 65 022