

**TOPSELLER -**  
many more available!

Live Tools


**heimatec**®

# Miyano


## ANX 42 SYY

| Part-#                                                  | Tool adaption          | Rotation<br>max [1/min] | Gear ratio | Coolant | Pressure<br>max. | Center<br>distance |
|---------------------------------------------------------|------------------------|-------------------------|------------|---------|------------------|--------------------|
| <b>Axial drilling and milling head</b>                  |                        |                         |            |         |                  |                    |
| 8 010 34 017                                            | <b>ER 16 A - u-tec</b> | 6.000                   | 1:1        | EXT     | --               | --                 |
| 8 010 34 023                                            | <b>ER 16 A - u-tec</b> | 12.000                  | 1:1        | IC/Ext  | 100 bar          | --                 |
| 8 010 34 022                                            | <b>ER 20 A - u-tec</b> | 6.000                   | 1:1        | EXT     | --               | --                 |
| 8 010 34 025                                            | <b>ER 20 A - u-tec</b> | 12.000                  | 1:1        | IC/Ext  | 100 bar          | --                 |
| <b>Radial drilling and milling head</b>                 |                        |                         |            |         |                  |                    |
| 8 030 34 048                                            | <b>ER 16 A - u-tec</b> | 12.000                  | 1:1        | IC/Ext  | 140 bar          | <b>59 mm</b>       |
| 8 030 34 049                                            | <b>ER 16 A - u-tec</b> | 12.000                  | 1:1        | EXT     | --               | <b>59 mm</b>       |
| 8 030 34 045                                            | <b>ER 20 A - u-tec</b> | 12.000                  | 1:1        | IC/Ext  | 140 bar          | <b>59 mm</b>       |
| 8 030 34 046                                            | <b>ER 20 A - u-tec</b> | 12.000                  | 1:1        | EXT     | --               | <b>59 mm</b>       |
| <b>Radial drilling and milling head, double spindle</b> |                        |                         |            |         |                  |                    |
| 8 039 34 006                                            | <b>ER 16 u-tec</b>     | 12.000                  | 1:1        | EXT     | --               | <b>59 mm</b>       |
| <b>Universal head, offset</b>                           |                        |                         |            |         |                  |                    |
| 8 043 34 002                                            | <b>ER 16 A - u-tec</b> | 6.000                   | 1:1        | EXT     | 140 bar          | <b>50 mm</b>       |
| 8 043 34 003                                            | <b>ER 16 A - u-tec</b> | 6.000                   | 1:1        | IC/Ext  | 25 bar           | <b>50 mm</b>       |
| 8 043 34 013                                            | <b>ER 16 A - u-tec</b> | 6.000                   | 1:1        | EXT     | 140 bar          | <b>66 mm</b>       |
| 8 043 34 014                                            | <b>ER 16 A - u-tec</b> | 6.000                   | 1:1        | IC/Ext  | 25 bar           | <b>66 mm</b>       |


Illustrations similar.




8 010 34 017



8 030 34 048



8 039 34 006



8 043 34 002

**TOPSELLER -**  
many more available!

Static Tools


**heimatec**®

# Miyano

## ANX 42 SYY

| Part-#                                   | Tool adaption           | Coolant | Pressure max. | Center distance |
|------------------------------------------|-------------------------|---------|---------------|-----------------|
| <b>Universal turning holder</b>          |                         |         |               |                 |
| 8 224 04 071                             | <b>Sq. 20</b>           | IC/Ext  | 140 bar       | --              |
| <b>Boring bar holder</b>                 |                         |         |               |                 |
| 8 240 08 035                             | <b>Ø 32</b>             | IC/Ext  | --            | <b>60 mm</b>    |
| <b>Combi double turning holder</b>       |                         |         |               |                 |
| 8 251 04 041                             | <b>Sq. 20</b>           | IC/Ext  | 140 bar       | --              |
| <b>Multiple boring bar holder</b>        |                         |         |               |                 |
| 8 253 07 048                             | <b>Ø 25</b>             | IC/Ext  | --            | --              |
| <b>Cut-off holder, height adjustable</b> |                         |         |               |                 |
| 8 320 03 019                             | <b>Clampshaft SH 32</b> | IC/Ext  | 70 bar        | --              |


*Illustrations similar.*



8 224 04 071



8 240 08 035



8 251 04 041



8 253 07 048